

NO ONE DELIVERS MORE



2023 Product Line Brochure





Hyundai Forklifts

With our growing line of innovative forklifts and our new, expanded parts depot located in Atlanta, Hyundai provides dealers and their customers with unmatched product support, warranty administration, technical training, parts inventory, and rapid parts delivery.

Backed by the global manufacturing, research, and development resources of Hyundai Construction Equipment, one of the world's most trusted industrial brands, Hyundai Material Handling meets the needs of the North American marketplace with a full line of high-performance forklifts – including diesel, electric, and LPG models, ranging from 2,200 to 55,000 lb. (997 to 24,947 kg) capacity. All part of our unyielding commitment to make certain that when it comes to meeting the material handling needs of business, No One Delivers More.





ELECTRIC FORKLIFTS



Photos may include optional equipment.



ELECTRIC RIDER FORKLIFTS



15/18/20BCS-9



15/18/20BT-9U

Item		Stand Up Counter Balance Forklifts			Three Wheel Forklift 36V/48V (3,000 - 4,000 lbs capacity)			
Model		15BCS-9	18BCS-9	20BCS-9	15BT-9U	18BT-9U	20BT-9U	
Identification	Load capacity	lb	3,000	3,500	4,000	3,000	3,500	4,000
	Load center	in	24			24	24	24
Weights	Service weight	lb	8,514	8,922	9,283	6,889	7,419	7,716
	Axle loading, loaded front / rear	lb	9,797 / 1,717	10,970 / 1,585	11,603 / 1,680	9,098 / 1,098	10,141 / 1,246	10,803 / 1,323
	Axle loading, unloaded front / rear	lb	4,380 / 4,133	4,411 / 4,511	4,554 / 4,729	3,662 / 3,228	3,770 / 3,649	3,713 / 3,997
Wheels, Chassis	Tire Type	Cushion			Solid Pneumatic			
	Overhead guard height	in	87.9	87.9	87.9	81.3		
Dimension	Length to face of forks	in	67.99	67.99	70.7	74.2	77.8	79.1
	Overall width	in	42	42	42	42.3	43.5	43.5
	Turning radius	in	55	55	57.7	60.6	64.2	65.4
	Right-angle stacking aisle width 40 x 48 in*	in	120.3	120.3	123	127	130.6	131.9
	Right-angle stacking aisle width 32 x 48 in*	in	125.1	125.1	127.8	131.9	135.4	136.8
Performance	Travel speed loaded / unloaded	mph	7.5	7.5	7.5	9.9 / 10.6		
	Drive motor rating	HP	5.8 x 2			6.3 x 2		
	Pump (lift) motor rating	HP	18.8			18.8		
	Battery voltage	V	36 / 48			36 / 48	36 / 48	36 / 48
	Battery compartment (L/W/H)	in	38.38 / 17.95 / 31.49	38.38 / 17.95 / 31.49	38.8 x 20.71 x 31.49	38.7 / 21.7 / 27.6 (25.6)	38.5 / 25.1 / 27.6 (25.6)	38.5 / 25.1 / 27.6 (25.6)
Others	Type of drive control	AC						

*Allow six inches for safe distance when turning and stacking.
 () Side Loading Type



ELECTRIC RIDER FORKLIFTS



25/30/32BC-9



16/20B-9



25/30/32/35B-9U

Item			Four Wheel Forklift Cushion Tire 36V/48V (5,000 - 6,000 lbs. capacity)			Four Wheel Forklift Pneumatic Tire 36V/48V (3,200-7,000 lbs. capacity)					
			25BC-9	30BC-9	32BC-9	16B-9	20B-9	25B-9U	30B-9U	32B-9U	35B-9U
Identification	Model		25BC-9	30BC-9	32BC-9	16B-9	20B-9	25B-9U	30B-9U	32B-9U	35B-9U
	Load capacity	lb	5,000	6,000	6,500	3,200	4,000	5,000	6,000	6,500	7,000
	Load center	in	24	24	24	24	24	24	24	24	24
Weights	Service weight	lb	9,733	10,736	11,199	6,945	7,672	9,612	10,214	10,626	11,067
	Axle loading, loaded front / rear	lb	13,261 / 1,984	15,104 / 2,247	15,898 / 2,357	9,259 / 1,213	10,692 / 1,389	13,262 / 1,861	15,018 / 1,808	15,642 / 2,039	16,616 / 2,167
	Axle loading, unloaded front / rear	lb	3,774 / 5,959	4,098 / 6,638	4,090 / 7,033	3,494 / 3,450	3,638 / 4,034	3,979 / 5,633	4,445 / 5,769	4,365 / 6,261	4,301 / 6,845
Wheels, Chassis	Tire Type		Cushion Tire			Solid Pneumatic		Solid Pneumatic			
	Overhead guard height	in	88			81.3		87.8			
Dimension	Length to face of forks	in	86.8	92.3	92.3	80.1	83.9	90.4	97.8	98.5	102
	Overall width	in	43.7	44	44	42.3	43.5	47.2	47.2	47.2	49.2
	Turning radius	in	76.2	82.5	82.5	63.7	71.3	76.4	84.6	85.2	86.8
	Right-angle stacking aisle width 40 x 48 in*	in	141.6	147.8	147.8	132	135.7	143.2	150.7	151.3	153.4
	Right-angle stacking aisle width 32 x 48 in*	in	149.3	155.6	155.6	137.6	141.5	149.7	157.8	158.4	160.5
Performance	Travel speed loaded / unloaded	mph	10.6 / 11.2			9.9 / 10.6		10 / 11			
	Drive motor rating	HP	18.8			6.3 x 2		7 x 2			
	Pump (lift) motor rating	HP	22.8			18.8		22.8			
	Battery voltage	V	36/48	36/48	36/48	36/48	36/48	36/48	36/48	36/48	36/48
	Battery compartment (L/W/H)	in	39.8 / 30.4 / 24.8(23.7)	39.8/30.4/24.8(23.7)	39.8/30.4/24.8(23.7)	38.5 / 21.7 / 27.6 (25.6)	38.7 / 25.1 / 27.6 (25.6)	40.7 / 31.5 / 22.2 (21.1)	40.7 / 39.4 / 22.2 (21.1)	40.7 / 39.4 / 22.2 (21.1)	40.7 / 39.4 / 22.2 (21.1)
Others	Type of drive control	AC									

*Allow six inches for safe distance when turning and stacking () Side Loading Type



ELECTRIC RIDER FORKLIFTS



25/30/35BH-9



40/45/50B-9

Item		Four Wheel - Pneumatic Tire 80V (4,400-10,000 lbs. capacity)						
		25BH-9	30BH-9	35BH-9	40B-9	45B-9	50B-9	
Identification	Model							
	Load capacity	lb	5,000	6,000	7,000	8,000	9,000	10,000
	Load center	in	24	24	24	24	24	
Weights	Service weight	lb	10,384	11,310	12,357	15,113	16,193	17,207
	Axle loading, loaded front / rear	lb	13,977 / 1,918	15,955 / 1,969	17,756 / 2,317	21,050 / 2,881	23,052 / 3,062	24,983 / 3,225
	Axle loading, unloaded front / rear	lb	5,115 / 5,269	5,655 / 5,655	5,686 / 6,671	7,725 / 7,388	8,060 / 8,133	8,331 / 8,876
Wheels, Chassis	Tire Type	Solid Pneumatic			Solid Pneumatic			
Dimension	Overhead guard height	in	87	87	87	91.3		
	Length to face of forks	in	93.1	98.2	102.4	117.9	117.9	119.7
	Overall width	in	44.0		53.9		53.9	56.1
	Turning radius	in	75.8	80.9	84.4	105.1	105.1	106.5
	Right-angle stacking aisle width 40 x 48 in*	in	138.4	144.3	144.7	173.4	173.4	175.0
Right-angle stacking aisle width 32 x 48 in*	in	145.4	151.6	152.1	181.3	181.3	182.9	
Performance	Travel speed loaded / unloaded	mph	11.2/11.8			10.6 / 10.6		
	Drive motor rating	HP	10.7 X 2			13.4 x2		
	Pump (lift) motor rating	HP	26.8			37.5		
	Battery voltage	V	80	80	80	80	80	80
	Battery compartment (L/W/H)	in	40.6 / 28.1 / 31.5 (31.3)	40.6 / 33.8 / 31.5 (31.3)	40.6 / 33.8 / 31.5 (31.3)	40.6 / 39.5 / 32.2 (31.3)	40.6 / 39.5 / 32.2 (31.3)	40.6 / 39.5 / 32.2 (31.3)
Others	Type of drive control	AC						

*Allow six inches for safe distance when turning and stacking.
() Side Loading Type



ELECTRIC FORKLIFTS - NARROW AISLE



13BOP-7



13BOP-9



15/18/20/23BRP-9

Item		Order Picker			Pantograph Reach Forklift				
Identification	Model	13BOP-7	13BOP-9	13BOP-9 (addl lift)	15BRP-9 (Double Reach)	18BRP-9	20BRP-9	23BRP-9	
	Load capacity	lb	3,000	3,000	2,200	3,000	3,500	4,000	4,500
	Load center	in	24			24			
	Operator Type	Standing			Standing				
Weights	Service weight	lb	6,398	6,470	6,786	8,781	7,408	7,727	8,600
	Axle loading, loaded front/rear	lb	1,872 / 7,525	1,634 / 7,701	1,970 / 7,081	7,143 / 4,639	7,031 / 3,878	7,762 / 3,964	8,576 / 4,524
	Axle loading, unloaded front/rear	lb	3,583 / 2,813	3,448 / 3,020	3,393 / 3,393	3,512 / 5,269	2,879 / 4,528	3,045 / 4,683	3,406 / 5,194
Wheels, Chassis	Tire Type (load/drive/caster)	Polyurethane/Solid rubber			Polyurethane/Solid rubber				
	Service brake	Electromagnetic brake			Electromagnetic brake				
Dimension	Overhead guard height	in	89		94.3	94.3	94.3	94.3	
	Reach stroke	in	N / A		42.8	23.3	23.3	23.3	
	Outrigger inner dimension/BR, BRJ overall width (load end/drive end)	in	41.3		42	42	42	42	
	Turning radius (in standard battery compartment)	in	71.6		73.1	65.6	67.4	71.6	
Performance	Travel speed loaded/unloaded	mph	9.5 / 10.0	7.5	7.3 / 7.3				
	Drive Motor Rating	HP	5.2	5.8	9.1				
	Pump (lift) motor rating	HP	14.2	12.2	21.4				
	Maximum battery voltage	V	36/48	24	36 / 48	36 / 48	36 / 48	36 / 48	
	Battery compartment		38.3 / 16.5 / 32.5	38.26 x 16.33 x 31.1		Varies based on compartment type			
Others	Type of drive control	AC							



ELECTRIC FORKLIFTS - NARROW AISLE



15/18/20/25BR-X



14/16/20/25BRJ-9

Item		Moving Mast Reach Forklift								
		15BR-X	18BR-X	20BR-X	25BR-X	14BRJ-9	16BRJ-9	20BRJ-9	25BRJ-9	
Identification	Model									
	Load capacity	lb	3,000	3,500	4,000	5,000	2,800	3,200	4,000	5,000
	Load center	in	24				24			
	Operator Type		Standing				Seated			
Weights	Service weight	lb	5,051	5,093	6,137	6,389	6,980	7,185	8,375	8,873
	Axle loading, reach-in, unloaded front/rear	lb	1,790 / 3,260	1,649 / 3,444	2,167 / 3,971	1,997 / 4,392	4,180 / 2,800	4,442 / 2,743	4,954 / 3,422	5,593 / 3,280
	Axle loading, reach-out, unloaded front/rear	lb	7,308 / 1,049	8,027 / 1,034	9,385 / 1,161	10,666 / 1,235	1,327 / 8,739	1,345 / 9,367	1,391 / 11,393	1,517 / 12,868
	Axle loading, reach-in, loaded front/rear	lb	5,573 / 2,787	5,635 / 3,425	6,826 / 3,721	7,145 / 4,755	3,554 / 6,512	3,871 / 6,841	4,200 / 8,587	5,229 / 9,153
Wheels, Chassis	Tire Type (load/drive/caster)	Polyurethane/Solid rubber/Solid rubber				Polyurethane/Solid rubber/Solid rubber				
	Service brake	Disc				Electric	Disc	Disc	Disc	
Dimension	Overhead guard height	in	89.6	89.6	90.3	90.3	83.3	83.3	84.1	84.1
	Reach stroke	in	17.6	26.2	26.2	31.8	19.8	21.8	21.4	27.2
	Outrigger inner dimension/BR, BRJ overall width (load end/drive end)	in	30.4 / 42.1	30.4 / 42.1	30.8 / 46.9	30.8 / 46.9	50.4 / 50.0	50.4 / 50.0	50.8 / 50.0	53.1 / 50.0
	Turning radius (in standard battery compartment)	in	62.8	69.9	70.5	78.0	64.5	66.3	68.6	74.2
Performance	Travel speed loaded/unloaded	mph	6.2/6.2	6.2/6.2	6.6/6.5	6.5/6.5	8.7 / 8.7			
	Drive Motor Rating	HP	6				9.1			
	Pump (lift) motor rating	HP	12				20.1			
	Maximum battery voltage	V	36 / 48				36 / 48			
	Battery compartment		39.13 / 14.88 / 22.91				48.6 / 11.3 / 31.6	48.1 / 11.3 / 31.6	48.6 / 14.1 / 31.6	48.6 / 14.1 / 31.6
Others	Type of drive control	AC								



LPG FORKLIFTS



Photos may include optional equipment.



LPG FORKLIFTS - CUSHION TIRE



25/30/33LC-9

Item		LPG Forklifts - Cushion Tire (3,000-6,000 lbs. capacity)			
		25LC-9	30LC-9	33LC-9	
Identification	Model				
	Load capacity	lb	5,000	6,000	6,500
	Load center	in	24	24	24
Weights	Service weight	lb	8,694	9,556	10,098
	Axle loading, loaded front/rear	lb	12,151 / 1,547	13,666 / 1,889	14,715 / 1,887
	Axle loading, unloaded front/rear	lb	3,570 / 5,124	3,376 / 6,180	3,563 / 6,536
Wheels, Chassis	Tire size, front		21 x 7 x 15	21 x 8 x 15	21 x 8 x 15
	Tire size, rear		16 x 6 x 10.5	16 x 6 x 10.5	16 x 6 x 10.5
Dimension	Overhead guard height	in	81.3	81.3	81.3
	Length to face of forks	in	89.8	92.2	93.9
	Overall width	in	42.1	43.7	43.7
	Ground clearance, loaded, under mast	in	3.54	3.5	3.54
	Turning radius	in	80	82	82.7



LPG FORKLIFTS - PNEUMATIC TIRE



15/18/20L-7M



25/30/33L-9A 35LN-9A

Item			LPG Forklifts - Pneumatic (3,000-4,000 lbs. capacity)			LPG Forklifts - Pneumatic (5,000-7,000 lbs. capacity)		
			15L-7M	18L-7M	20L-7M	25L-9A	30L-9A	35LN-9A
Identification	Model							
	Load capacity	lb	3,000	3,500	4,000	5,000	6,000	7,000
	Load center	in	24	24	24	24	24	24
Weights	Service weight	lb	5,930	6,305	6,712	8,203	9,074	9,998
	Axle loading, loaded front/rear	lb	8,024 / 1,212	8,031 / 1,334	9,656 / 1,468	12,273 / 1,812	14,054 / 1,997	15,304 / 2,407
	Axle loading, unloaded front/rear	lb	2,623 / 3,307	2,528 / 3,777	2,438 / 4,274	3,527 / 5,044	3,675/5,765	3,194 / 6,801
Wheels, Chassis	Tire size, front		6.5 x 10 x 12PR	6.5 x 10 x 12PR	6.5 x 10 x 12PR	7 x 12 x 14PR	28 x 9.15 x 14PR	28 x 9.15 x 14PR
	Tire size, rear		5 x 8 x 10PR	5 x 8 x 10PR	5 x 8 x 10PR	6.5 x 10 x 12PR	6.5 x 10 x 12PR	6.5 x 10 x 12PR
Dimension	Overhead guard height	in	83.1	83.1	83.1	85	85.8	85.8
	Length to face of forks	in	87.9	89.1	90.9	102.6	105.3	108.5
	Overall width	in	42.1	42.1	42.1	47	48.3	48.3
	Ground clearance, loaded, under mast	in	4.7	4.7	4.7	5	5.7	5.7
	Turning radius	in	78.7	79.8	81.1	92	95	98
Performance	Travel speed, unloaded	mph	12.5			11.5	12.4	11.7
	Engine manufacturer / model		HYUNDAI / L4KB			HYUNDAI / L4KB		
	Engine power	HP	50			60		
	Rated speed	1/min	2,450			2,300		
	No. cylinder / cubic capacity	/cc	4 / 2,359			4 / 2,359		
	Service brake		Wet Disc			Wet Disc		



LPG FORKLIFTS - PNEUMATIC TIRE



35/40/45/50L-9



70L-7A

Item		LPG Forklifts - Pneumatic (8,000-11,000 lbs. capacity)				LPG Forklifts - Pneumatic (15,500 lbs. capacity)	
		35L-9	40L-9	45L-9	50L-9	70L-7A	
Identification	Model						
	Load capacity	lb	7,716	8,818	9,920	11,023	15,500
	Load center	in	24	24	24	24	24
Weights	Service weight	lb	12,789	13,995	14,746	15,560	20,790
	Axle loading, loaded front/rear	lb	17,978 / 2,526	19,978 / 2,835	21,817 / 2,851	23,585 / 2,998	32,110 / 4,110
	Axle loading, unloaded front/rear	lb	5,787 / 7,002	6,045 / 7,950	6,418 / 8,332	6,389 / 9,172	8,5230 / 12,270
Wheels, Chassis	Tire size, front		8.25 x 15 -14	7.5 x 16 x 12	7.5 x 16 x 12	7.5 x 16 x 12	8.25 x 15
	Tire size, rear		7 x 12 -14	7 x 12 x 14	7 x 12 x 14	7 x 12 x 14	8.25 x 15
Dimension	Overhead guard height (Opt)	in	87 (92)				98.4
	Length to face of forks	in	122.5	124.6	129.3	131.8	142.5
	Overall width	in	54	68.5	68.5	68.5	82.2
	Ground clearance, loaded, under mast	in	6.7	6.1	6.1	6.1	7.7
	Turning radius	in	112.9	114.8	118.5	120.2	132.7
Performance	Travel speed, unloaded	mph	19.1	18.6	18.5	18.4	14
	Engine manufacturer / model		KUBOTA / WG3800				PSI / 4.3
	Engine power	HP	91				94
	Rated speed	1/min	2,300				2,300
	No. cylinder / cubic capacity	/cc	4 / 3,800				6 / 4,294
	Service brake		Wet Disc				



DIESEL FORKLIFTS



Photos may include optional equipment.

DIESEL FORKLIFTS



25/30/33D-9 35DA-9



35/40/45D-9F 50DA-9F



35/40/45D-9 50DA-9

Item		Diesel Forklifts														
		25D-9	30D-9	33D-9	35DA-9	35D-9F	40D-9F	45D-9F	50DA-9F	35D-9	40D-9	45D-9	50DA-9			
Identification	Model															
	Load capacity	lb	5,000	6,000	6,500	7,000	8,000	9,000	10,000	11,000	8,000	9,000	10,000	11,000		
	Load center	in	24	24	24	24	24	24	24	24	24	24	24	24		
Weights	Service weight	lb	8,572	9,440	10,055	10,357	12,994	14,193	15	15,199	16,089	13,082	14,295	15,212	16,131	
	Axle loading, loaded front/rear	lb	12,273 / 1,802	14,054 / 1,997	15,007 / 2,324	15,648 / 2,425	18,082 / 2,628	20,082 / 2,930	21,757 / 3,362	23,558.5 / 3,554	17,948 / 2,851	20,078 / 3,034	21,806 / 3,327	23,541 / 3,611		
	Axle loading, unloaded front/rear	lb	3,527 / 5,044	3,675 / 5,765	3,589 / 6,466	3,541 / 6,817	5,890.7 / 7,323.7	6,148.6 / 8,044.6	6,082.5 / 9,116	6,139.8 / 9,949.5	5,756 / 7,326	6,144 / 8,148	6,131 / 9,081	6,124 / 10,005		
Wheels, Chassis	Tire size, front		7 x 12 x 14PR			28 x 9 -15,14PR		8.25 x 15 -14PR		7.5 x 16 -12PR			8.25 x 15 x 14PR		7.5 x 16 -12PR	
	Tire size, rear		6.5 x 10 x 14PR			6.5 x 10 -14PR		7 x 12 x 12PR			7 x 12 x 12PR		7.0 x 12 x 14PR			
Dimension	Overhead guard height	in	85			85.8		87.4 (92)			87	87	87	87		
	Length to face of forks	in	102.6	105.4	107.6	108.9	122.4	127	128.5	130	127	127	129	130		
	Overall width	in	47.2			48.3		54 (68.5)			54 Single (68.5 Dual)	54 Single (68.5 Dual)	54 Single (68.5 Dual)	54 Single (68.5 Dual)		
	Ground clearance, loaded, under mast	in	5.1			5.7		6.7	6			6.7	6.1			
	Turning radius	in	92.2	95	97	98	113	114.8	116.7	118.5	116	116	118	118		
Performance	Travel speed, unloaded	mph	11.5			12.4		16.5	16	15.9		16.5	16	15.9		
	Service brake		Wet Disc Brake				Wet Disc Brake				Wet Disc Brake					
	Engine manufacturer/model		KUBOTA / V3307				KUBOTA / V3800				CUMMINS / QSF3.8					
	Engine power	HP	67				74.27				101					
	Rated speed	1/min	2,300				2,200				2,200					
	No. cylinder / cubic capacity	/cc	4 / 3,331				4 / 3,769				4 / 3,726					
	Fuel consumption rate	g/h	0.85	0.9	0.95	N/A	5.3	5.4	5.5	5.6	1.61	1.64	1.69	1.72		

DIESEL FORKLIFTS



50/70/80D-9/100-9V

110/130/160D-9

160D-9L/180D-9B

250D-9

Item		Diesel Forklifts										
		50D-9	70D-9	80D-9	100D-9V	110D-9	130D-9	160D-9	160D-9L	180D-9B	250D-9	
Identification	Model											
	Load capacity	lb	11,000	15,500	17,400	22,000	25,000	29,000	35,000	36,000	40,000	55,116
	Load center	in	24	24	24	24	24	24	24	48	36	48
Weights	Service weight	lb	19,599	23,091	25,591	28,763	35,880	37,459	43,746	52,810	52,810	81,617
	Axle loading, loaded front/rear	lb	26,792 / 3,730	33,347 / 5,011	38,034 / 5,384	44,961 / 5,801	52,823 / 7,308	59,029 / 7,090	70,568 / 8,453	82,559 / 5,525	86,379 / 6,113	126,274 / 92,030
	Axle loading, unloaded front/rear	lb	9,940 / 9,557	9,757 / 13,166	11,310 / 14,484	12,401 / 16,361	17,758 / 18,120	17,611 / 19,848	20,825 / 22,919	26,599 / 26,209	26,599 / 26,209	41,110 / 40,508
Wheels, Chassis	Tire size, front		8.25 x 15 x 14PR		9 x 20 x 14PR	9 x 20 x 14PR	10 x 20 -16PR		12 x 20 x 18PR	12 x 20 x 20PR		14 x 24 x 32PR
	Tire size, rear		8.25 x 15 x 14PR		9 x 20 x 14PR	9 x 20 x 14PR	10 x 20 -16PR		12 x 20 x 18PR	12 x 20 x 20PR		14 x 24 x 32PR
Dimension	Overhead guard height	in	102.2	102.2	103.9	105.5	115.9	115.9	117.3	121	121	126.9
	Length to face of forks	in	138.5	144.3	156.3	167.9	179.9	180.3	200.0	219	219	250.5
	Overall width	in	82.2	82.2	86.4	89.2	96.5	96.5	98.3	100	100	120.1
	Ground clearance, loaded, under mast	in	7.7	7.7	9.8	9.8	9.8	9.8	9.8	9.6	9.6	11.8
	Turning radius	in	130.5	135.3	145.7	156.1	171.3	171.3	192.7	205.5	205.5	230.9
Performance	Travel speed, unloaded	mph	21.1	20.9	21.7	20.3	22.1	22.1	21.9	21.8	21.8	19.6
	Service brake		Wet Disc Brakes				Wet Disc Brakes			Wet Disc Brakes		Wet Disc Brakes
	Engine manufacturer/model		CUMMINS /QSF3.8				CUMMINS /QSB6.7				CUMMINS QSL	
	Engine power	HP	101		101	120	164			163		274
	No. cylinder / cubic capacity	/cc	4 / 3,800		4 / 3,800		4 / 3,726		6 / 6,690		6 / 8,898	
	Fuel consumption rate	g/h	2.14	2.19	2.25	1.3	2.93	3.01	3.20	3.2		6.60



Hyundai Material Handling North America

**Hyundai Construction Equipment
Americas, Inc.**

6100 ATLANTIC BOULEVARD
NORCROSS, GA 30071
U.S.A.

TEL (1) 678-823-7777
FAX (1) 678-823-7778

©2022 Hyundai Material Handling. All Rights Reserved.
Printed in U.S.A.

Supported by a comprehensive network of more than 150 dealer and branch locations across the US and Canada, Hyundai Material Handling is committed to offering the industry's most innovative equipment solutions, exceptional parts availability, fast delivery, and professionally trained technical support to our dealers and their customers.

When it comes to rugged, reliable, innovative equipment and superior service and support No One Delivers More.

